

**YUMAX® P-329**  
**General Purpose**  
**Rust Preventative**

**PRODUCT DATA SHEET**

**GENERAL DESCRIPTION:**

**YUMAX® P-329** is a solvent based rust preventative product formulated with wax and petrolatum. **YUMAX® P-329** forms a waxy protective film, 8-11 microns thick, that protects parts from corrosion for 6 months or more. **YUMAX® P-329** is frequently chosen for rust protection of super-finished bearing parts and other in-process parts that are stored for extended periods between processes.

**BENEFITS:**

- **EXCELLENT CORROSION PROTECTION -OVER 6 MONTHS**
- **NON-STAINING PROTECTIVE FILM**
- **EXCELLENT WATER DISPLACING CHARACTERISTICS**
- **EASILY REMOVED WITH KEROSENE OR ALKALINE CLEANER**

**PROPERTIES:**

Appearance.....	Light Brown Suspension
Film Type.....	Waxy
Specific Gravity (15°/4°C) .....	0.84
Viscosity (40°C).....	6.8 mm <sup>2</sup> /s
Color (ASTM) .....	L8.0
Flash Point (PMCC) .....	42°C
Film Thickness .....	8 to 11 microns
Non Volatile.....	45 wt%

**COMBUSTIBLE: Keep away from open flame and sparks.**

**USING PROCEDURES:**

**YUMAX® P-329** is to be used full strength for best results. Typically, parts are dipped into a tank containing **YUMAX® P-329** to completely coat all exposed surfaces. However, it may be applied via brush or spray if desired. A drain plug should be located in the bottom of the tank to facilitate the regular draining of water.

**MATERIAL SAFETY:**

Safe on metals when used as directed.

**CONCENTRATION CONTROL:**

Not applicable.

**STORAGE:**

Store in a cool dry area away from heat and flames.

**PRECAUTIONS:**

Please refer to the label and Material Safety Data Sheet for all warnings, recommendations for safety equipment and other regulatory information.

**AVAILABILITY:**Pails, Drums, Totes, Bulk